

XY2CD111

Simple rope pull switch, Telemecanique
Emergency stop rope pull switches XY2C,
cable 240 VAC 10 A XY2Cd



Main

| | |
|---------------------------|--|
| Range of product | Telemecanique Emergency stop rope pull switches XY2C |
| Product or component type | Simple rope pull switch |
| Device short name | XY2CD |
| Housing colour | Blue |
| Overtoltage category | Class I conforming to IEC 61140 Class I conforming to NF C 20-030 |

Complementary

| | |
|--|---|
| Trigger cable maximum length | 6 m |
| Body material | Zamak |
| Head material | Plastic |
| [Us] rated supply voltage | 240 V |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Snap action |
| Resistance to wrenching | 237 DaN operating head 36 daN operating ring |
| Cable entry number | 3 3 entries tapped for Pg 11 cable gland for Pg 11 |
| Mechanical durability | 1500000 cycles |
| [Ie] rated operational current | 3 A at 240 V, AC-15, A300 conforming to IEC 60947-5-1 appendix A 0.27 A at 250 V, DC-13, Q300 conforming to IEC 60947-5-1 appendix A |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 400 V (pollution degree 3) conforming to IEC 60947-1 300 V conforming to UL 508 300 V conforming to CSA C22.2 No 14 |
| Compatibility code | XY2CD |

Environment

| | |
|---------------------------------------|------------------------------|
| Product certifications | CCC[RETURN]CE |
| Ambient air temperature for operation | -20...70 °C |
| IP degree of protection | IP66 conforming to IEC 60529 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.200 cm |
| Package 1 Width | 6.500 cm |
| Package 1 Length | 14.600 cm |
| Package 1 Weight | 285.000 g |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 16 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 15.000 cm |

| | |
|------------------|-----------|
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 4.745 kg |

Offer Sustainability

| | |
|--|---|
| Sustainable offer status | Green Premium product |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |