Product data sheet Characteristics

ZCMD21L08R12

Limit switch body, Limit switches XC Standard, ZCMD, 1NC+1 NO, silver, snap action, connection, M12 0.8 m



Main

Series name Series name Product or component type Device short name Design Body type Series name Device short name	Telemecanique Limit switches XC Standard Standard format Limit switch body CCMD Miniature Tixed CCEF0
Product or component type Device short name Z Design M Body type F	Cimit switch body CCMD Miniature Fixed
type Device short name Z Design Body type F	ZCMD Miniature
Design M Body type F	//iniature Fixed
Body type F	ixed
Associated head 7	7CEE0
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	CCE14 CCE27 CCE28 CCE01 CCE11 CCE02 CCE21 CCE06 CCE09 CCE24 CCE61 CCE62 CCE66 CCE62 CCE66 CCE62 CCE65 CCE65 CCE64 CCE63 CCE63 CCE63 CCE67 CCE67 CCE67 CCE67
Body material Z	Zamak
Number of poles 2	2
Contacts type and 1 composition	NC + 1 NO
Contact operation S	Snap action

Complementary

Complementary		
Product compatibility	XCMD	
Electrical connection	Remote male connector M12, 5 pins	
Cable length	0.8 m	
Wire insulation material	PvR	
Contacts insulation form	Zb	
Contacts material	Silver plated contacts	
Positive opening	With	
Minimum actuation speed	0.01 m/min	
[le] rated operational current	0.22 A at 50 V, DC-13 conforming to EN/IEC 60947-5-1 appendix A 3 A at 50 V, AC-15 conforming to EN/IEC 60947-5-1 appendix A	
[Ithe] conventional enclosed thermal current	4 A	
[Ui] rated insulation voltage	60 V (pollution degree 3) conforming to IEC 60947-5-1	
Maximum resistance across terminals	25 mOhm conforming to IEC 60255-7 category 3	
[Uimp] rated impulse withstand voltage	0.8 KV conforming to IEC 60664 0.8 kV conforming to IEC 60947-1	
Short-circuit protection	4 A cartridge fuse, type gG	

Electrical durability	5000000 Cycles, DC-13 24 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 2 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Width	30 mm
Height	50 mm
Depth	16 mm
Net weight	0.065 kg

Environment

Ambient air temperature for storage	-4070 °C		
-------------------------------------	----------	--	--

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.27 cm
Package 1 Width	12.7 cm
Package 1 Length	19.3 cm
Package 1 Weight	120 g
Unit Type of Package 2	S03
Number of Units in Package 2	70
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	8.275 kg
Unit Type of Package 3	P06
Number of Units in Package 3	560
Package 3 Height	75 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	74 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months

